

ST400i Cordless Fence Post Stapler

The ST400i is the worlds first 4mm diameter / 9 Gauge cordless fencing stapler that makes fencing faster, easier and more safer for the fencer/fencing contractor.

The ST400i Cordless Fencing Stapler is just as powerful as our popular Pneumatic ST400 fencing stapler but is not reliant on compressors and hoses. After listening to our customers, we have engineered this tool to help you be even more efficient during the day. This fencing stapler will revolutionize stapling in the fencing industry. It is safe and allows you to fire staples with one hand, allowing you to keep your second hand out of harms way.

The ST400i has outstanding power allowing you to fire up to 650 staples per fuel cell and in conjunction with the 3.7V Li-ion battery, you can fire 3000 staples per charge per battery. The ST400i kit also comes with 2 batteries so you will never run out of power.

This fencing stapler is compatible with the Power Staple Insulator Guide Attachment allowing you to easily erect an electric fence by using the PEL Wood Post Claw Insulators (sold seperately).

Features

Portable, no need for compressors or air lines

Fast, high output design

Drives up to 2 staples per second

Ergonomic Design

Comfort for periods of high use

Hose free for work in remote situations

Adjustable Depth of Drive

Greater flexibility for staple placement and a superior finish

Prevents damage to wire

Suitable for 40mm, 45mm and 50mm Length Staples

Ideal for rural wire and batten fencing applications

Suitable for 4.0mm Diameter Staples

Quick Clear Nose

Less downtime if fastener jams occur

Top Load Magazine

Easy and fast re-loading

Rail protection bars

Sequential Trigger System

Improved operator safety

V-Notch Guide and Wire Guide

Ensures correct staple placement for improved holding power



Specifications	Details
Product Code	ST4iAP1
Product Size (WxHxD)	4.33" x 14.56" x 16.92" (110mm x 370mm x 430mm)
Packaged Size (WxHxD)	6.29" x 18.50" x 20.07" (160mm x 470mm x 510mm)
Tool Weight (with battery)	9.25 lbs (4.2kg)
Packaged Weight	17.63 lbs (8.0kg)
Quantity Per Pack	1
Cycle Rate Per Second	2 staples per second
Magazine Capacity (Short)	50 staples (approx 2 strips)
Battery Capacity (Maximum)	Up to 3,000 staples per battery
Fuel Cell Capacity	Up to 500-650 staples per fuel cell
Staple Range Length	1 1/2", 1 3/4" and 2" (40mm, 45mm and 50mm)
Staple Diameter	9 Gauge (4.0mm)
Staple Type	Divergent point (hot dipped galvanised)
Battery	3.7V DC
Battery Recharge	2 hours
Fuel Cell	STOCKade Impulse Fuel Cell
Propellant	Liquid Hydrocarbon
Fuel Cell & Battery Storage Temperature	5°F to 120.2°F (-15°C to 49°C)
Rated Input Voltage Battery Charger	100-240V 50/60Hz AC or 10-16V DC
Rated Output Voltage Battery Charger	3.7V 2.1A

Pneumatic ST-400 Fencing Stapler

Features

Proven Pneumatic Technology

Adjustable power for high density timber
Reliability for high volume fence construction

Aluminium Alloy Housing

Lightweight and corrosion resistant for extreme durability

Rugged Driver Blade

Engineered specifically for driving heavy-duty fencing staples
Manufactured from high impact resistant steel for long life

Suitable for 40 to 50mm Length Fencing Staples

Uses genuine STOCK-ade barbed and non-barbed ST-400 staples
Ideal for heavy duty rural fencing applications

Suitable for 4.0mm Diameter Fencing Staples

STOCK-ade brand barbed and non-barbed available

Staple Wire Angle Guide

Custom nose locates the wire for speed and reliability

Adjustable Depth of Drive

Precision placement to prevent damage to fence wire

Top Load Magazine

Fast reloading to minimize down-time

Adjustable Air Deflector

Deflects discharged air away from operator for improved comfort

Sequential Trigger System

Superior operator safety

Swivel coupling

Greater flexibility for added convenience



Product Code	Description	Barcode
A12600	STOCK-ade Pneumatic 4.0mm Fencing Stapler	9315104015999

Pneumatic ST-400 Fencing Stapler

Specifications	A12600
Product Size (WxHxD)	120 x 360 390mm
Packaged Size (WxHxD)	135 x 440 x 530mm
Tool Weight	3.7kg
Packaged Weight	6.6kg
Quantity Per Pack	1
Cycle Rate	3 staples per second
Magazine Capacity	50 staples (2 strips)
Staple Range Length	40mm non-barbed divergent point 45 and 50mm barbed
Staple Range Diameter	4.00mm
Staple Type	Hot dipped pre-galvanised Bezinal 2000 240gm Heavy Coat
Collation Type	Paper collated
Operating Pressure	6.2 to 8.3bar (90 to 120psi)
Optimum Operating Pressure	6.75 to 7.24bar (98 to 105psi Hard Timber 110 to 120)
Noise Level	89 to 94dB
Air Consumption at 7bar (100psi)	2.2 Litres / cycle
Recommended Air Hose Fitting Diameter	10mm (3/8 to 1/2inch)

Applications	
	Rural livestock fencing
	Horticulture
	Rural heavy mesh and heavy woven fencing
	Predator control fencing
	Highway boundary fencing
	Rural utilities applications

ST400™

